



RC 209T - 04483



Capacity [uF]	Dimensions ^{*1} [mm]		
	D	L	L _L
0,5	30	56,5	250

*Other capacity on request

Applications:

R-C units are designed for use in DC and AC applications for contact protection and protection of power transistors and thyristors and triacs

Construction:

Metallized film capacitors noninductive construction. Self-healing ability. Cylindrical plastic case, epoxy resin sealed. With bottom-screw available

Capacity: 0,5uF

Resistors in range: 10 ÷ 1000Ω/2W
in accordance to customer specification.

Reference standards:

EN 130000, IEC 60384-14 ed.1993
and EN 132400

Rated working voltage:

U_R: 440V 50 Hz at +40°C
600VDC

Capacity: 0,5uF ± 20%

Resistor: 50Ω/2W

Insulation resistance between the leads:

R_{is} >10 GΩ

Climatic category IEC 60068

55/085/21

Construction of leads:

insulated stranded wire s = 0,5 mm²,
length L_L: 250 mm or on
customer specification

Marking for purchase ordering, sample:

RC 209T 0,5uF 50Ω/2W 440V 50/60Hz

Warning! The manufacturer is not responsible for any damages, caused by the improper installation and application. Before using the capacitor in any application, please, read carefully this technical data-sheet.